



# DATA SHEET JEMCO





الکتروموتور ۹۰۰ کیلووات ۱۰۰۰ دور ماشینهای الکتریکی جوبن (جمکو)

**Subject: Medium voltage squirrel cage induction motors**

|                                                |                              |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
|------------------------------------------------|------------------------------|------------------|--------------------|--------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------|--|--|--|
| Customer                                       |                              |                  |                    | Manufacturer <b>Jemco</b>                                                                                    |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Motor Type <b>YJS560-6</b>                     |                              |                  |                    | Average sound pressure level                                                                                 |                                                                                                                                                                                                                                                                      | No load | load |  |  |  |
| Frame Size <b>560</b>                          | Number of poles <b>6</b>     |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Mounting design <b>IM B3</b>                   | Type of encloser <b>IP55</b> |                  |                    | Direction of rotation both <input type="checkbox"/> CW <input type="checkbox"/> CCW <input type="checkbox"/> |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| EX-Protective syster <b>safe</b>               |                              |                  |                    | Bearing DE/NDE <b>6034M-C3+NU1034-C3 / NU322-C3</b>                                                          |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Duty type <b>S1</b>                            | Starting                     |                  |                    | Lubrication <b>Li Base Grease</b>                                                                            |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Ambient Temperture <b>40 C</b>                 |                              |                  |                    | Type of lubrication <b>K3N Din 51825</b>                                                                     |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Thermal classification <b>F</b>                | Tempertur rise <b>B</b>      |                  |                    | typical Test <b>IEC60034-1</b>                                                                               |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Term motor protection <b>optional</b>          |                              |                  |                    | outline dimention drawing No. <b>available</b>                                                               |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Retad output <b>900KW</b>                      |                              |                  |                    | Location of Terminal Box <b>optional</b>                                                                     |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| rated voltage <b>6000V+-5%</b>                 |                              |                  |                    | Additional Sensor <b>optional</b>                                                                            |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| connection <b>DELTA</b>                        |                              |                  |                    | space heater <b>optional</b>                                                                                 |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Ferquency <b>50 HZ.</b>                        | speed <b>993 rpm</b>         |                  |                    | Net weight approx. <b>6040 Kg+-10%</b>                                                                       |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Rated current <b>104 A</b>                     |                              |                  |                    | painting <b>RAL 7032</b>                                                                                     |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Starting Current $(I_A/I_N)$ <b>6.2</b>        |                              |                  |                    | Termal Protection <b>optional</b>                                                                            |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Power Factor                                   |                              | 4/4              | 3/4                | 1/2                                                                                                          | Additional Sensor <b>optional</b>                                                                                                                                                                                                                                    |         |      |  |  |  |
|                                                |                              | 0.88             |                    |                                                                                                              | Frame Material <b>Structural Steel</b>                                                                                                                                                                                                                               |         |      |  |  |  |
| Efficiency                                     |                              | 4/4              | 3/4                | 1/2                                                                                                          | Additional data and remarks:<br>1- permisslbie percentage Voltage imbalance not greater than1%<br>2-Cold Starting per Hour(3)<br>3- Hot Starting per Hour(2)<br>4- Maximum Hot starting Time not more than 60 second<br>5- Maximum cold Time not more than 80 second |         |      |  |  |  |
|                                                |                              | 94.8             |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Rated torque $(T_N)$                           |                              |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| starting torque $(T_s/T_N)=$ <b>0.70</b>       |                              |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Break-down torque $(T_{max}/T_N)=$ <b>1.82</b> |                              |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Rotor class/material <b>squirrel cage</b>      |                              | <b>copper</b>    |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Rotor voltage                                  |                              | Rotor current    |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| Rotor inertia                                  |                              | <b>1600 Kgm2</b> |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| cooling method                                 |                              | <b>IC411</b>     |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| altitude of instalation                        |                              | <b>1000m</b>     |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
|                                                | Date                         | Name             | Tolerances acc. To |                                                                                                              | NC.                                                                                                                                                                                                                                                                  |         |      |  |  |  |
| Designed                                       |                              |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |
| checked                                        |                              |                  |                    |                                                                                                              |                                                                                                                                                                                                                                                                      |         |      |  |  |  |

~3125



کلیه ابعاد بر حسب میلی متر است  
امکان تولید الکتروموتور بر طبق ابعاد مورد نظر مشتری وجود دارد.  
سایر ولتاژها نیز قابل طراحی و تولید می باشد.

[WWW.PARSTEHRAN.COM](http://WWW.PARSTEHRAN.COM)

Additional Information.:

## Electromotor 900 Kw-6Kv-6Pole

Type Of Construction:  
IMB3

Protection:  
IP55

Cooling:  
IC411

Sheet: 1/1

Size: A3

Drawn

Checked

Approved

Date

Jovain electrical machines Co.

(JEMCO)

Engineering Dept.

Title:

Outline drawing

Order No.:

YJS 560-6