



DATA SHEET JEMCO



الکتروموتور ۲۵۰ کیلووات ۱۰۰۰ دور ۶۰۰۰ ولت اسلیرینگ ماشینهای الکتریکی جوبن (جمکو)

Subject: Medium Voltage (6000V) Wound Rotor Motors

Customer				ManufacturerJemco			
Motor TypeYR1402-6AO				Average sound pressure level		No load	load
Frame Size400		Number of poles6					
Mounting designIM B3		Type of encloserIP55		Direction of rotationboth ☐ CW ☐ CCW ☐			
EX-Protective system safe				Bearing DE/NDENU324ECM-C3/6324-C3			
Duty typeS1		Starting		LubricationLi Base Grease			
Ambient Temperture		40 C		Type of lubricationK3N Din 51825			
Thermal classificationF		Tempertur riseB		typical TestIEC60034-1			
Term motor protection		optional		outline dimention drawing No.available			
Retad output250KW				Location of Terminal Boxoptional			
rated voltage6000V+-5%				Additional Sensoroptional			
connectionY				space heateroptional			
Ferquency50 HZ.		speed984 rpm		Net weight approx.3115 Kg+-10%			
Rated current30 A				paintingRAL 7032			
Rating Current of Roto (I _A /I _N)452				Termal Protectionoptional			
Power Factor		4/4	3/4	1/2	Additional Sensoroptional		
		0.82			Frame MaterialStructural Steel		
Efficiency		4/4	3/4	1/2	*In these motor series, production of electromotors are possible in the range of 3000~10000 Volt.		
		92.7					
Voltage of Rotor (T _N)			347		* Motor up 10MW can be manufactuerd according to customer order		
Rated torque (T _N)			2426				
Break-down torque (T _{max} /T _N)=			1.8		Additional data and remarks: 1- permisslbie percentage Voltage imbalance not greater than1% 2-Cold Starting per Hour(3) 3- Hot Starting per Hour(2) 4- Maximum Hot starting Time not more than 60 second 5- Maximum cold Time not more than 80 second		
Rotor class/materialsquirrel cage			copper				
Rotor voltage		Rotor current					
Starting Method		Oil Starter					
cooling method		IC611					
altitude of instalation		1000m					
	Date	Name	Tolerances acc. To		NO.		
Designed							
checked							

